

METHOflow

This product is made with fatty alcohols and ethoxylated derivatives and helps remove and prevent foam inside the fermentation system

100% biodegradable, thanks to the absence of silicone agents, which makes it safe to use.

Recommended for any type of foam

- Mainly fed with acid waste
- Fed with waste rich in fats
- High concentrations of ammoniacal nitrogen

DESCRIPTION

METHOflow helps reduce the surface tension in the fermented liquid, thereby allowing the gas to quickly exit the liquid fraction.

DIRECTIONS

METHOflow must be introduced into the tank or the fermentation system from above, directly on top of the foam. To make this operation easier, you can dilute **METHOflow** in water to obtain a 10% solution.

DOSES

2 to 20 g of **METHOflow**, depending on the amount of foam, every m3 of digestate or in the fermentation system or tanks.

SIZE

Available in 25-litre drums and 1000-litre barrels.



Methodo Chemicals is Positive Energy

Established in the '80s as a company
SELLING raw materials and additives for the animal feed
and dietary supplement industries.

During the '90s

the company built its PRODUCTION plant for making
premixes and complementary feed.

Today, METHODO

is putting its 30 years of experience in the nutrition sector
at your service to create a range of supplements that optimise
the anaerobic digestion process in BIOGAS plants.



FORMULATION, MANUFACTURING
OF COMPLEMENTARY FEEDS
AND PREMIXES TRADING
OF FEED MATERIALS
AND FEED ADDITIVES

METHODO CHEMICALS S.r.l.

Via A.M. Ampère, 19/21/23
42017 Novellara (RE) - Italy
Tel. +39 0522 / 6566 - Fax +39 0522 / 653549
www.methodochemicals.com

